



Kalrez® Spectrum™

From DuPont Performance Elastomers

Dow AgroSciences switches to O-rings of Kalrez® Spectrum™ 6375 and gains greatly extended seal lifetime



Kalrez® Spectrum™ 6375 perfluoroelastomer O-rings fitted to filling machine valves (seen here), processing aggressive solvents, surfactants and concentrated herbicides at Dow AgroSciences plant in France, provide at least 2 months operating lifetime, compared with seals of PTFE that fail in 24 hours.

By switching from O-rings of PTFE to DuPont Performance Elastomers Kalrez® Spectrum™ 6375 perfluoroelastomer parts at its plant in Drusenheim, France, Dow AgroSciences S.A. has seen seal lifetime increase from an average of one day to two months, leading to greater availability of its filling machines, major improvements in safety and reliability, reduced maintenance, and cost savings, reports Michel Blondel, mechanical maintenance leader at the plant (seen here).

Dow AgroSciences S.A., of Drusenheim, France, a global leader in pest management and biotechnology products, has recently extended the lifetime of dynamic and static seals fitted to its product filling line from one day to an average of *two months*, an improvement of some 6,000%, by replacing O-ring seals of PTFE with DuPont Performance Elastomers Kalrez® Spectrum™ 6375 perfluoroelastomer parts.

In a different application at the same plant, seals of FEP/FKM, fitted to the piston rod of a Type SRC Alfa Laval valve, failed regularly after only 8 hours operation. These seals have now been replaced by Kalrez® perfluoroelastomer parts. The result? Operating lifetime has now increased from 8 hours to between *8-12 months!*

The problem

The filling line at Dow AgroSciences plant in France processes aggressive solvents, surfactants and concentrated herbicides at temperatures ranging from 10 to 45°C, and pressures from 1.5 to 3.5 bars Eff. Filling machine valves on the line were fitted with dynamic PTFE O-ring seals, while the machine hoses were equipped with static O-rings, also of PTFE.

Michel Blondel, mechanical maintenance leader at the plant, explains the problem. "Each time we performed a clean-in-place procedure at 80°C, or made a product change on the filler, the PTFE seals became mechanically damaged. This meant we had to change the PTFE O-rings on a daily basis, since seal lifetime never extended beyond 24 hours before replacement."

The cost to Dow AgroSciences in extra performance time and maintenance had become unacceptable, and the company sought a much more resilient sealing material that would withstand frequent cleaning and product changes, and offer greatly extended seal lifetime.

Material chosen and why

In conjunction with one of our Kalrez® Authorized Distributors, Michel Blondel installed dynamic and static O-rings of Kalrez® Spectrum™ 6375 perfluoroelastomer to replace the PTFE seals, with dramatic and immediate improvement. Even more dramatic seal lifetime gains – from 8 hours to as much as 12 months – have been experienced by replacing FEP/FKM valve seals with Kalrez® perfluoroelastomer parts in another area of the plant, Mr. Blondel reports.

Kalrez® Spectrum™ 6375 is designed specifically for the chemical process industry. It provides outstanding performance in an extremely wide range of chemicals including acids, bases, amines and steam. The innovative patented curing system allows for continuous upper service temperatures of up to 275°C in applications such as mechanical seals, valves, flanges and pumps where elastomeric sealing is critical.

In addition, Kalrez® is a thermoset perfluoroelastomer and offers excellent elastic properties and resistance to mechanical damage, unlike PTFE which is a thermoplastic and appears to lack the necessary resilience to withstand mechanical shock in a process application such as this.

Benefits gained

Since switching to custom O-rings of Kalrez® Spectrum™ 6375, Dow AgroSciences S.A. reports an average seal lifetime of two months. That's an increase of approximately 6,000% over the previously fitted PTFE seals.

"Kalrez® Spectrum™ 6375 allows us to increase the operating uptime of our filling machines and to improve overall reliability of our packing line. We have also significantly reduced the time spent in O-ring replacement," says Michel Blondel.

He also reports cost savings as a result of major improvements in safety and reliability, and in reduced maintenance.

For further information please contact one of the offices below,
or visit our website at www.dupontelastomers.com

Global Headquarters – Wilmington, DE USA

Tel. +1 800 853 5515
+1 302 792 4000
Fax +1 302 792 4450

South & Central America Headquarters – Brazil

Tel. +55 11 4166 8978
Fax +55 11 4166 8989

Japan Headquarters – Tokyo

Tel. +81 3 5521 2990
Fax +81 3 5521 2991

European Headquarters – Geneva

Tel. +41 22 717 4000
Fax +41 22 717 4001

Asia Pacific Headquarters – Singapore

Tel. +65 6275 9383
Fax +65 6275 9395

The information set forth herein is furnished free of charge and is based on technical data that DuPont Performance Elastomers believes to be reliable. It is intended for use by persons having technical skill, at their own discretion and risk. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any material, evaluation of any compound under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents. While the information presented here is accurate at the time of publication, specifications can change. Check www.dupontelastomers.com for the most up-to-date information.

Caution: Do not use in medical applications involving permanent implantation in the human body. For other medical applications, discuss with your DuPont Performance Elastomers customer service representative and read Medical Caution Statement H-69237.

DuPont™ is a trademark of DuPont and its affiliates.
Kalrez® is a registered trademark of DuPont Performance Elastomers.
Kalrez® Spectrum™ is a trademark of DuPont Performance Elastomers.

Copyright © 2005 DuPont Performance Elastomers.
All rights reserved.

Printed in Switzerland
KZE-D10648-00-B1005

DuPont 
Performance Elastomers